# SSC-301-X SPECIFICATIONS

## LARGE WALL HANDSET TELEPHONE FOR RING-DOWN OPERATION

### Standard Analog Power, but also available in VoIP versions

Vandal resistant stainless steel wall mount telephone for ring-down operation. The telephone will accept incoming calls and relies on external equipment to control calling. Equipped with marine quality chrome mechanical hookswitch, instruction or advertising window, ID window, 32" hearing aid compatible armored cord handset with internal steel lanyard, which is anchored into housing for added strength, tamper resistant security screws, and mounting backplate.



#### **SPECIFICATIONS**

Panel Size: 7.5" W x 21" H x 4.10" D 6.5" D With handset on Hook

Weight: Approximately 16 lbs.

Mounting Instructions: Vertical Surface Mount: Separate the cover

assembly from the backplate The backplate assembly is designed to be mounted on any flat vertical surface. Four mounting holes are

provided

**Environment:** Temperature: -30°C (-22°F) to 60°C (140°F)

Humidity: 0%-90% non-condensating

Input Power:Telephone Line PoweredLoop Current:23mA min to 80mA max


Impedance:600 ohmsType Jack:RJ11CRinger Equivalency:0.4A

Hearing Aid Compatible: Meets EIA standards

UL & FCC Registration: Certified

ACCESSORIES: 301-037 Security Tool

(required for installation)



-M	-IVC	-ACH**	-ACH*	-CCH*	-RIL	-RIS
To	(VOLUME *)	3	)))	3	0	grate
Sealed Magnetic Hookswitch Completely Sealed No Moving Parts	Push Button Volume Control  Background Noise reducer	Other Length armored cord from 12" to 72"(inches). Example: -ACH12 12" Long	ACHW-White Handset ACHR-Red Handset (Black is standard)	Coiled cord available from 5', 10', & 15' (feet). Example: -CCH5 5' Long	Ring Indicator Light located on the phone panel for visual ring indication	Ring Indicator Flashing Blue Light (Requires AC Power)



#### Providing Telecommunication Solutions Since 1930

Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http://www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006